

NOTES

1-1/4" to 2-1/4" SQUARE BAR PRODUCTS:

1. Included Connection Hardware:

SS125 1-1/4" Material:	5/8" diameter bolt (2 per coupling) per SAE J429 Grade 8 and nuts.
SS1375 1-3/8" Material:	3/4" diameter bolt (2 per coupling) per SAE J429 Grade 8 and nuts.
SS5 and SS150 1-1/2" Material:	3/4" diameter bolt per ASTM A325 and nut.
SS175 1-3/4" Material:	7/8" diameter bolt per ASTM A193 Grade B7 and nut.
SS200 2" Material:	1-1/8" diameter bolt per ASTM A193 Grade B7 and nut.
SS225 2-1/4" Material:	1-1/4" diameter bolt per ASTM A193 Grade B7 and nut.
2. Catalog numbers with an * after the number are lead sections that have been designed with a longer shaft above the top helix for the Helical Pulldown[®] Micropile.
3. The letter "T" after the helix diameter stands for 1/2" thick helix material.
4. All helices are spaced 3 times the diameter of the preceding helix unless otherwise specified by the customer.
5. The standard helix has a flat faced leading edge. In the above charts the helices of the lead sections with SLE in the "Helix Edge" column have sharpened leading edges.
6. Sea shell cut helices are available in 45⁰, 90⁰ and 120⁰.
7. All products are hot dip galvanized per ASTM A153.
8. For plain steel and/or special order items contact your area CHANCE[®] Civil Construction Distributor for availability.